

PAVEMENT MARKING

LEGEND

SIGN ON PERMANENT SUPPORT

GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS, AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

ON MULTI-LANE ROADS THE TRANSVERSE BANDS SHOULD EXTEND ACROSS ALL APPROACH LANES, AND INDIVIDUAL R X R SYMBOLS SHOULD BE USED IN EACH APPROACH LANE.

CENTER OR LANE LINES AND NO-PASSING ZONE MARKINGS SHOWN ON THIS DRAWING ARE REQUIRED AND PAID FOR UNDER

TRACE EXISTING SYMBOL WHERE EXISTING SYMBOLS ARE PLACED.


- (1) MINIMUM 8' FROM ANY RAILROAD WARNING DEVICES (SIGNAL, GATES, ETC.) OR 25' FROM THE NEAREST RAIL, WHICHEVER DISTANCE IS GREATER.
- 2) 500' MINIMUM. MARKING LIMITS MAY BE EXTENDED AS DIRECTED BY THE ENGINEER TO MEET ADJACENT NO-PASSING ZONE
- (3) FOR MULTIPLE TRACK CROSSINGS, THE BARRIER LINE SHALL EXTEND TO THE NEAR RAIL OF THE FURTHEST TRACK IN THE DIRECTION OF HIGHWAY TRAVEL.

DISTANCE TABLE

TABLE BASED UPON 2C-4 WISCONSIN SUPPLEMENT OF MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

POSTED SPEED (M.P.H.)	DIMENSION RANGE (FEET)	
25	150 * - 250'	
30	200 * - 300'	
35	250 * - 450'	
40	300 * - 500' 400 * - 650'	
45		
50	550 * - 800'	
55	750 * - 1000'	
60	1000 [*] - 1250'	
65	1000 [*] - 1250'	

* THE MINIMUM DISTANCES IN THE TABLE ARE DESIRABLE AND SHOULD BE USED. THE DISTANCES MAY BE INCREASED UP TO THE MAXIMUM TO ALLOW FOR FIFLD CONDITIONS SUCH AS THE CLOSED PROXIMITY OF DRIVEWAYS, BRIDGES, SIDE ROADS OR OTHER FEATURES THAT WOULD PROHIBIT THE MINIMUM DISTANCES FROM BEING USED.



SIGNING AND PAVEMENT MARKING DETAILS FOR RAILROAD - HIGHWAY GRADE CROSSINGS

STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION

APPROVED February 2021 DATE

/S/ Matthew R. Rauch STATE SIGNING AND MARKING ENGINEER

SDD 15C09

500 Version 12

Standard Detail Drawing 15C9 (sheet a)

February 2021

Signing and Pavement Marking Details for Railroad - Highway Grade Crossings

Reference:

Traffic Engineering, Operations and Safety Manual Chapter 3 (<u>TEOpS Chapter 3</u>) Manual on Uniform Traffic Control Devices Part 8B

Bid items associated with this drawing:

<u>ITEM</u> <u>NUMBER</u>	DESCRIPTION	<u>UNIT</u>
646.5305	Marking Railroad Crossing Paint	EACH
646.5320	Marking Railroad Crossing Epoxy	EACH

Standard Special Provisions associated with this drawing:

STSP NUMBER TITLE

NONE

Other SDDs associated with this drawing:

SDD 15C8 (a,b) Pavement Marking (Mainline and Turn Lanes)

Design Notes:

Refer to Part 8 of the Wisconsin Manual on Uniform Traffic Control Devices to determine when railroad crossings require markings. Preferred option is intended for all new construction, including overlay projects. The alternative option is for remarking operations unless directed otherwise.


Contact Person:

Jeannie Silver (608) 246-5408 Ryan Mayer (608) 246-3810

GENERAL NOTES

SIGNING AND MARKING IS SHOWN AS TYPICAL PLACEMENT. FIELD CONDITIONS MAY DICTATE CHANGES IN SIGNING AND MARKING PLACEMENT.

- 1 INSTALLED FOR EXPRESSWAYS
- 2 3' LINE, 9' GAP, EXCEPT RETRACE THE EXISTING LINE GAP PATTERN WHERE EXISTING MARKINGS
- ** SEE SDD 15C09-a, "SIGNING AND PAVEMENT MARKING DETAILS FOR RAILROAD HIGHWAY GRADE



DETAIL FOR TRUCK STOPPING LANE PAVEMENT MARKINGS



TRUCK STOPPING LANE PAVEMENT MARKINGS

STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION

February 2021 DATE

SDD 15C09

5C09 SDD /S/ Matthew R. Rauch

Version 12 Standard Detail Drawing 15C9 (sheet b) February 2021

Railroad Truck Stopping Lane Pavement Markings

Reference:

Traffic Engineering Operations and Safety Manual Chapter 3 (<u>TEOpS Chapter 3</u>) Manual on Uniform Traffic Control Devices Part 3B

Bid items associated with this drawing:

<u>UNIT</u>	<u>DESCRIPTION</u>	<u>ITEM</u> NUMBER
	ed with this drawing in addition to those shown on sheet a:	Bid items associate
LF	Marking Line Paint 8-Inch	646.3005
	Marking Line Epoxy 8-Inch	646.3020
	Marking Line Grooved Wet Ref Epoxy 8-Inch	646.3040
	Marking Line Grooved Permanent Tape 8-Inch	646.3050
LF	Marking Line Grooved Wet Ref Contrast Epoxy 8-Inch	646.3545
LF	Marking Line Grooved Contrast Permanent Tape 8-Inch	646.3555

Standard Special Provisions associated with this drawing:

STSP NUMBER TITLE

NONE

Other SDDs associated with this drawing:

<u>SDD 15C8</u> Pavement Marking sheet "a" (mainline) is required.

Design Notes:

Refer to Sheet "a".

Contact Person:

Jeannie Silver (608) 246-5408 Ryan Mayer (608) 246-3810